

IBM TotalStorage Ultrium Tape Drives T800 and T800F



IBM TotalStorage Ultrium Tape Drives T800 and T800F

The third-generation IBM TotalStorage® Ultrium Tape Drives T800 (SCSI) and T800F² (Fibre Channel) are designed to help meet the storage challenges faced by IT organizations today. First, there is the enormous growth in data, fueled by business continuity, regulatory compliance and information lifecycle management initiatives. Then, there are initiatives to improve IT operations, such as infrastructure simplification, improved administrative productivity and more reliable, cost-effective data protection.

Highlights

- **Offers a data transfer rate of up to 160 MBps¹ to help shorten backup times**
- **Provides a cartridge capacity of up to 800GB¹ to address the need to store ever greater amounts of data**
- **Designed to be backward compatible with previous-generation Ultrium™ tape drives and media to help protect prior investments**
- **Designed to provide adaptive data compression, Digital Speed Matching (DSM) and a 128MB buffer for optimal performance and storage capacity**
- **Available with either an Ultra160 SCSI or 2GB Fibre Channel² interface for flexible attachment**
- **Incorporates new tape threading features, redesigned electronics and error correction functions designed to enhance drive robustness and reliability**

Greater capacity and speed

Offering up to twice the capacity and more than double the performance of the preceding Ultrium 2 generation of drives, the T800 and T800F tape drives are designed for integration into servers, desktop enclosures, autoloaders and scalable automated tape libraries.

To further increase capacity, Digital Speed Matching (DSM) is designed to adjust the drive's native data rate to better match the data rate of the server. This feature, along with a larger 128MB buffer, is designed to help improve data throughput and reduce tape repositions in an environment where the host data rate is less than optimal.

In addition, the T800 and T800F tape drives use an IBM-patented compression algorithm for optimal compression. The compression algorithm is designed to synchronously swap the data compression scheme dynamically between ALDC (adaptive lossless data compression) and a pass-thru mode. While data compression is being performed, a separate circuit—designed to perform simultaneous decompression—helps support data integrity.

Compatibility with prior-generation Ultrium media

Compatibility with prior-generation Ultrium tape media eases the introduction of higher-performance tape drives, helping to protect prior investments in drives, media and tape automation systems. The T800 and T800F drives are backward read and write compatible with Ultrium 2 media and read compatible with Ultrium 1 media. By using

Ultrium 3 media, you can further shorten backup and restore times, reduce the number of tapes required and further improve the backup window.

Flexible host attachment

All three generations of IBM Linear Tape-Open (LTO) tape drives support either SCSI or native Fibre Channel attachment. The T800 and T800F tape drives are designed to allow stand-alone servers to exploit the tape drive when natively attached. The T800F tape drive allows deployment into second-generation storage area network (SAN) environments, supporting both the Fibre Channel-Arbitrated Loop (FC-AL) topology as well as direct connection to a fabric port on a Fibre Channel fabric such as a McDATA switch.

SAN and library integration

The T800F tape drive is designed to auto-configure to establish its operational mode (FC-AL or point-to-point) and attachment speed. The T800F tape drive features advanced library support (LDI or ADI)² through an RS-422 connector. This is designed to allow the drive to respond quickly to library commands and help avoid contention on the attachment bus.

Greater data protection with reliability and serviceability enhancements

Several new features have been added to the T800 and T800F tape drives to help improve overall reliability. The new independent tape loader and threader motors combine with positive pin retention improvements to increase the reliability of loading, recovering and tape extraction during a sudden power down. In addition, enhancements made to the Partial Response Maximum Likelihood (PRML) channel include an adaptive channel calibration feature. This feature is designed to compensate for variations in the recording function, media and read/write head to help optimize interchangeability between LTO vendors' drives.

Despite the dramatic increases in performance, the T800 and T800F tape drives consume less power than previous generations of IBM LTO tape drives. Highly integrated electronics use IBM copper-based technology to help reduce power consumption. These lower power requirements are particularly important for systems in which heat dissipation must be limited.

For enhanced serviceability, the T800 and T800F drives are designed to capture error information which is stored in flash memory. During a power outage, this information can help reduce troubleshooting time for IT staff as well as for system manufacturers.

Low total cost of ownership

The high performance and capacity of the IBM TotalStorage Ultrium Tape Drives T800 and T800F can help reduce the number of tape cartridges, tape drives and tape libraries required in a storage environment. Compatibility with prior generations of Ultrium media makes it possible for customers to easily migrate to this new generation.

Enhancements in third-generation drives

The T800 and T800F tape drives introduce new features that can help increase throughput, capacity and reliability over previous generation LTO drives—while also helping to protect critical data.

- ***A new 16-channel head design*** is designed to help provide double data throughput while maintaining backward compatibility with previous generation drives. The new 16-channel head, coupled with the 31 percent increase in linear density, increases drive performance.
- ***Enhanced, IBM-patented, timing-based servo positioning*** is designed to help data be written to tape with greater precision. The tracks are narrower on the new 16-channel head which helps to increase cartridge capacity. Compared to the T400/T400F, the track density of the T800/T800F is increased by 37.5 percent to 704 tracks.
- ***A new tape loader and threader mechanism*** helps improve error recovery when loading, threading and unloading a cartridge. Independent loader and threader motors, coupled with positive pin retention, help retain the pin during a mis-pick. This independent control can help improve load and thread reliability.
- ***A graceful dynamic braking feature*** helps enable the reel motors to gradually decelerate instead of stopping abruptly in the event of a power failure. It helps prevent tape stretching and loose tape wraps and can reduce tape damage and breakage.
- ***“On-the-fly” adaptive channel calibration*** is designed to allow the drive to adjust to variations in the media and head. Calibrating the channel can help improve higher data throughput rates and data integrity among LTO vendors’ drives.
- ***Redesigned electronics*** Even though the number of tracks have doubled, the overall power consumption of the drive has been reduced from that of previous generation LTO drives.
- ***A redesigned head actuator*** is designed to help provide greater resiliency to shock and vibration. This provides improved read head tracking capability and performance.
- ***Enhanced power management*** results in reduced heat dissipation and greater operational efficiency than that of previous generation LTO drives. The drive operates in two modes: write mode and idle mode (for when the drive is not in use).
- ***Digital Speed Matching (DSM)*** is supported on Ultrium 3 media in increments of 40 MBps to 80 MBps. This feature, along with a larger buffer, is designed to help improve throughput in environments where the host data rate is less than optimal.

- **A larger 128MB buffer** is designed to work in combination with DSM to mask the impact of data rate fluctuations, allowing the tape drive to perform at its optimal speed.
- **WORM support**³ To help meet the needs of evolving regulatory compliance initiatives, the T800 & T800F tape drives will adopt the LTO industry specification for WORM. WORM-enabled drives are designed to automatically determine whether the inserted cartridge is a WORM (write once, read many) or read/write cartridge. WORM cartridges provide the ability to store vital customer data in a non-erasable, non-rewriteable format.

Media

You can order media for all your IBM TotalStorage Ultrium tape products from your IBM Representative or IBM Authorized Distributor. Or visit ibm.com/servers/storage/media

For more information

Contact your IBM representative or IBM Business Partner or visit:

ibm.com/servers/storage/tape/oem

IBM TotalStorage Ultrium Tape Drives T800 and T800F at a glance

Characteristics

Tape drive type	LTO Ultrium 3
Capacity per cartridge	800GB compressed ¹ ; 400GB native
Data transfer rate	Up to 160 MB/sec compressed ¹ ; 80 MB/sec native
Number of tracks	704
Media	LTO Ultrium 1, 2 and 3
Data cartridge	LTO Ultrium 3: Part number 24R1922
Universal cleaning cartridge	For LTO Ultrium 1, 2 and 3: Part number 35L2086
Backward compatibility	Read/write compatible with Ultrium 2 media Read compatible with Ultrium 1 media
Interface	T800: Ultra160 SCSI LVD T800F: FC-2 at 1 Gb/sec or 2 Gb/sec
Library interface	LDI, ADI ²
Data compression	SLDC (LTO data compression per ECMA-321) ⁴
Buffer	128MB
Rewind speed	Up to 8 meters/sec
Operating speed	5.44 meters/sec
Data rate matching	Digital Speed Matching 40 MB/sec, 50 MB/sec, 60 MB/sec, 70 MB/sec, 80 MB/sec
Locate speed	8 meters/sec
Average file access	54 seconds
Load to BOT	15 seconds
Unload from BOT	15 seconds
Average rewind time	55 seconds

Physical characteristics

Dimensions (internal drive)	8.5 cm H x 14.9 cm W x 21.1 cm D (3.33 in x 5.83 in x 8.33 in)
Weight	3.0 kg (6.6 lb)

Reliability

Mean time between failures (MTBF)	250,000 hours at 100 percent duty cycle*
Error rate (calculated)	1 x 10 ¹⁷ bytes per permanent read error*
Error rate (validated)	1 x 10 ¹⁴ bytes per permanent read error* 1 x 10 ¹³ bytes per permanent write error*

Operating environment

Operating temperature	10° to 40° C (50° to 100° F)
Relative humidity	20% to 80% (non-condensing)
Electrical power	T800: 5 V at 3.3 A, 12 V at 1.1 A (steady state)
Power dissipation	T800: 10 W (idle, with cartridge), 28 W (read/write)

Open systems support

Microsoft® Windows® 2000; Microsoft Windows Server™ 2003; Sun Solaris 8, 9; HP-UX 11.0, 11i; Linux® (Red Hat Enterprise Server 3, SUSE LINUX Enterprise Server 8; AIX® Version 5L 5.1, 5.2, 5.3; and Novell NetWare)

Warranty

Three-year mail-in exchange

* All performance and reliability values are provided 'AS IS' and no warranties or guarantees are expressed or implied by IBM. Actual values may vary and depend upon many factors including system hardware configuration and software design and configuration.



© Copyright IBM Corporation 2004

IBM Systems and Technology Group
9000 South Rita Road
Tucson, AZ 85744

Produced in the U.S.A.
December 2004
All Rights Reserved

IBM, the IBM logo, AIX and TotalStorage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both.

Linear Tape-Open, LTO and Ultrium are trademarks of International Business Machines Corporation, Hewlett-Packard and Certance.

Intel is a trademark of Intel Corporation in the United States, other countries or both.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows and Windows NT are trademarks of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.

MB, GB and TB equal 1,000,000, 1,000,000,000 and 1,000,000,000,000 bytes, respectively, where referring to storage capacity. Actual storage capacity will vary based upon many factors and may be less than stated. Some numbers given for storage capacities give capacity in native mode followed by capacity using data compression technology.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS-IS" WITHOUT ANY WARRANTY, EITHER EXPRESSED OR IMPLIED. IBM EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements (e.g., IBM Customer Agreement, Statement of Limited Warranty, International Program License Agreement, etc.) under which they are provided.

References in this document to IBM products, programs or services does not imply that IBM intends to make such products, programs or services available in all countries in which IBM operates or does business. Any reference to an IBM program or product in this document is not intended to state or imply that only that program may be used. Any functionally equivalent program or product that does not infringe IBM's intellectual property rights may be used instead. It is the user's responsibility to evaluate and verify the operation of any non-IBM product, program or service.

¹ Assuming 2:1 compressible data.

² Availability is currently planned for the first quarter of 2005.

³ Availability is currently planned for the second quarter of 2005.

⁴ Prior to the release of ECMA-321, SLDC (streaming lossless data compression) was known as "LTO-DC." SLDC uses ALDC as its primary data compression scheme, but also has a pass-thru scheme to avoid the expansion of incompressible data—a problem ALDC and most other compression algorithms encounter.

⁵ Depending upon configuration.