



Ref. Certif. No.

US-32101-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

AC/DC Power Supplies

Name and address of the applicant

QUALSTAR CORPORATION
130 W COCHRAN ST, SUITE C
SIMI VALLEY CA 93065 USA

Name and address of the manufacturer

N2POWER INC.,
A SUBSIDIARY OF QUALSTAR CORPORATION
130 W COCHRAN ST, SUITE C
SIMI VALLEY CA 93065 USA

Name and address of the factory

Note: When more than one factory, please report on page 2

WANWANG ELECTRONICS (SHENZHEN) CO LTD
NO 20 YUANHU RD ZHANGBEI AILIAN LONGGANG DISTRICT
SHENZHEN GUANGDONG 518172
CHINA

Additional Information on page 2

Ratings and principal characteristics

Input (for all Models except SMP75):
100-240 V, 3.5 A , 50-60 Hz
See Page 2

Trademark (if any)



Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

SMP75, XL275-3 @, XL275-5 @, XL275-6 @, XL275-7 @,
XL275-v @
See Page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN 62368-1:2014 / A11:2017;
National Differences specified in the CB Test Report.

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

E211115-A6001-CB-2 issued on 2018-07-18

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-07-19

Signature:

Jolanta M. Wroblewska



Ref. Certif. No.

US-32101-UL

Model Details:

XL275-3 @, XL275-5 @, XL275-6 @, XL275-7 @, XL275-v @

where v denotes the output voltage (V1) between 12 - 56 Vdc and @ may be any alphanumeric characters or blank, not affecting safety related constructions or critical components.

Ratings:

Input (for all Models except SMP75):

100-240 V, 3.5 A, 50-60 Hz

Input (for Model SMP75):

100-240 V AC, 3.6-1.5 A, 50-60 Hz

Output:

XL275-3 @:

V1 = 12 Vdc / 22.9 A

V2 = 12 Vdc / 1.0 A

V3 = 5 Vdc stby / 1A

XL275-5 @:

V1 = 24 Vdc / 11.5 A

V2 = 12 Vdc / 1.0A

V3 = 5 Vdc stby / 1A

XL275-6 @:

V1 = 48 Vdc / 5.7 A

V2 = 12 Vdc / 1.0 A

V3 = 5 Vdc stby / 1A

XL275-7 @:

V1 = 56 Vdc / 4.9 A

V2 = 12 Vdc / 1.0 A

V3 = 5 Vdc stby / 1A

XL275-v @:

V1 = 12-56 Vdc / 22.9-4.9 A

V2 = 12 Vdc / 1 A

V3 = 5 Vdc stby / 1A

SMP75

V1 = 30 Vdc / 9.16 A (High Line 240 V, 275 W); 30 Vdc / 7.5 A (Low Line 100 V, 225 W)

V2 = n/a

V3 = n/a

stby = Stand By

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-07-19

Signature:

Jolanta M. Wroblewska