

## US-32102-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)

### **CB TEST CERTIFICATE**

**Product** AC/DC Power Supplies

Name and address of the applicant QUALSTAR CORPORATION 130 W COCHRAN ST, SUITE C

SIMI VALLEY CA 93065 USA

Name and address of the manufacturer N2POWER INC.,

A SUBSIDIARY OF QUALSTAR CORPORATION

130 W COCHRAN ST, SUITE C SIMI VALLEY CA 93065 USA

Name and address of the factory PANYU TRIO MICROTRONICS CO LTD

SHIJI INDUSTRIAL ESTATE DONGYONG NANSHA

**GUANGZHOU GUANGDONG 511453** 

**CHINA** 

Additional Information on page 2

Ratings and principal characteristics 100-277 Vac, 4.5 A, 47-63 Hz - or -

100-240 Vac, 4.5 A, 47-63 Hz

See Page 2

N2Power Trademark (if any)

Type of Customer's Testing Facility (CTF) Stage used

Note: When more than one factory, please report on page 2

Model / Type Ref. XL375-12 CS S148, XL375-xx @ See Page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN 62368-1:2014 / A11:2017; National Differences specified in the CB Test Report. Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

E211115-A6002-CB-2 issued on 2018-07-18

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Signature: Date: 2018-07-19

Jolanta M. Wroblewska



# US-32102-UL

### Model Details:

XL375-xx @,

where "xx" denotes the output voltage (V1) between 12-60 Vdc and @ may be any alphanumeric character or blank, for marketing purpose only and no impact safety related constructions and critical components. May be followed by LED indicated changes in secondary circuit, see Model Difference for explanation.

#### **Factories**

WANWANG ELECTRONICS (SHENZHEN) CO LTD

NO 20 YUANHU RD ZHANGBEI AILIAN LÖNGGANG DISTRICT SHENZHEN GUANGDONG 518172 CHINA

### Ratings:

Input:

100-277 Vac, 4.5 A, 47-63 Hz - or -100-240 Vac, 4.5 A, 47-63 Hz

### Output:

V1 = designated by "xx" in model nomenclature

A1 = 358 Watts/V1 A

V2 = 12 Vdc

A2 = 1 A

V3 = 5 Vdc (stand-by)

A3 = 1 A

# Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-07-19

Signature:

Jolanta M. Wroblewska