



Qualstar LTO-7 Tape Drive

Seventh-generation LTO Ultrium tape drive

Highlights

- Provide long-term backup and archival storage for data while lowering overall storage costs
 - Simplify data management with IBM® Spectrum Archive™ utilizing IBM Linear Tape File System™ (LTFS) technology
 - Improve energy efficiency over previous generations.
 - Support media partitioning on Linear Tape-Open (LTO) Ultrium 7 media.
-

The Qualstar LTO-7 Tape Drive is the answer to growing storage requirements and shrinking backup windows. Incorporating the latest generation of industry leading LTO technology, the Qualstar LTO-7 tape drive is suited for handling backups, save and restore, and archival data storage needs with higher capacity and higher data transfer rates than previous LTO generations. In addition, the LTO Ultrium 7 technology is designed to support media partitioning and IBM Spectrum Archive technology. It also continues to support encryption of data and write-once-read-many (WORM) media. Qualstar's LTO-7 Tape Drive will help organizations handle the growing data demands of modern tape use cases like big data, cloud computing, Internet of Things (IoT), media and entertainment, digital video surveillance, active file archiving and, of course, for backup.

The LTO-7 Tape Drive is an excellent tape storage solution for organizations requiring backup and low cost, archival storage of data. The LTO-7 Tape Drive provides a physical storage capacity of up to 15 TB (with 2.5:1 compression). The data transfer performance has increased over the previous LTO Ultrium generation with an uncompressed data transfer rate of up to 300 MB/s (up to 900 MB/s with 2.5:1 compression) with either 8 Gb/s FC or 6 Gbps SAS interface connectivity.



Systems

Data Sheet

Advanced features

The LTO-7 8 Gb/s FC or 6 Gbps SAS interfaces enables it to connect to a wide spectrum of open-system servers. The LTO Ultrium 7 tape media provides partitioning support, which, in conjunction with LTFS or other third party software programs, provides users with file-level access to tape data. This support helps users quickly locate and update information on the tape media.

The LTO Ultrium 7 technology is also designed to support data encryption. The hardware encryption and decryption core and control core reside in the LTO Ultrium 7 Tape Drive.

Software support

You can increase the power of the LTO-7 Tape Drive by managing it with tape management solutions such as IBM Spectrum Protect or other third-party storage software applications.

Archiving enables storage of digital assets for the long term, so assets can be referenced and monetized for years to come.

Anyone who needs fast and reliable access to inactive, 'cold,' data—like movie and music producers, post production editors, broadcasters, digital video surveillance managers, and cloud and storage managers—now has an affordable solution to access and more easily archive high-quality files. LTFS opens the door to new uses and applications for LTO Ultrium tape, making tape easy and intuitive



Media

The LTO-7 Tape Drive supports the LTO Consortium compressed specification for LTO Ultrium 7 at 15 TB of data per cartridge (6 TB native). This capacity is 2.4 times the compressed capacity of the previous LTO Ultrium 6 cartridge. In addition to reading and writing to LTO Ultrium 7 tape cartridges, the LTO-7 Tape Drive can read and write to LTO Ultrium 6 cartridges and can read LTO Ultrium 5 cartridges.



Qualstar LTO-7 Tape Drive at a glance

Available configuration	8 Gb/s FC; 6 Gbps SAS
Tape drive type	LTO Ultrium 7
Physical capacity	6 TB native; 15 TB with 2.5:1 compression
Number of tape drives	1
Number of tape cartridges	1
Data transfer rate	Up to 300 MB/s native, up to 750 MB/s with 2.5:1 compression
Media Type	<p>Read and write: LTO Ultrium 7 6 TB data cartridge 6 TB WORM cartridge</p> <p>LTO Ultrium 6 2.5 TB data cartridge 2.5 TB WORM cartridge</p> <p>Read only: LTO Ultrium 5 1.5 TB data cartridge 1.5 TB WORM cartridge</p> <p>Also available: LTO Ultrium cleaning cartridge</p>
Weight	5 kg / 10 lbs (Full Height) 4 kg / 8 lbs (Half Height)
Power Requirements	100 – 240 V ac, 50 – 60 Hz auto-ranging
Dimensions	254mm x 508mm x 203mm; 10" x 20" x 8" (Full Height) 381mm x 279mm x 127mm; 15" x 11" x 5" (Half Height)



Why Qualstar?

The capacity, speed and reliability of your backup and archiving solutions are critical to your business processes, along with the performance of your storage infrastructure as a whole. Qualstar offers market-leading experience to help you handle the storage challenges that your network or company faces with a broad portfolio of proven hardware and solutions offerings. Innovative technology in tune with recent innovations, a commitment to open standards and high performance—all backed by Qualstar with its recognized expertise—are just a few of the reasons why you should consider Qualstar storage offerings.

For more information

To learn more about Qualstar LTO-7 Tape Drives please contact your Qualstar representative or Qualstar Partner, or visit: www.qualstar.com



Qualstar Corporation
130 W. Cochran Street;
Suite C
Simi Valley, CA 93065

Produced in the United States of America
March 2018

Linear Tape-Open, L TO, and Ultrium are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

This document is current as of the initial date of publication and may be changed by Qualstar at any time. Not all offerings are available in every country.

The performance data discussed herein is presented as derived under specific operating conditions. Actual results may vary.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT. Qualstar products are warranted according to the terms and conditions of the agreements under which they are provided.

Actual available storage capacity may be reported for both uncompressed and compressed data and will vary and may be less than stated.



Please Recycle